

What is a Sunny Boy battery inverter?

The Sunny Boy Storage 3.7/5.0/6.0 is a high-performance SMA battery inverter for private homes. Larger storage systems are easy to implement and are flexible to expand with a total of three battery connections. A PV system and the corresponding storage system is as unique as its user's power consumption and home.

How many battery connections does the Sunny Boy Storage have?

With three battery connections in total, the Sunny Boy Storage grows with the individual needs of its users. Maybe in the near future, you want to charge your electric vehicle in a climate-neutral manner and for free with electricity from your own PV system. Or you want to supply a heat pump with self-generated solar power.

How do I Commission the Sunny Boy Storage?

The Sunny Boy Storage can be commissioned quickly and easily via a smartphone, tablet or PC in a few steps and thanks to an integrated web interface. Tech Tip: How to commission the Sunny Boy Storage 3.7, 5.0, 6.0? Refueling and heating for free What actually sets the big brother apart from Sunny Boy Storage 2.5?

Wir haben vorhin in einem anderen Thread diskutiert, ob es technische Unterschiede zwischen den SBS 3.7, 5.0 und 6.0 gibt. Bei einphasigem Netzparallelbetrieb in Deutschland darf sowohl der SBS 5.0, als ...

technical data (preliminary) Sunny Boy Storage 3.7 Sunny Boy Storage 5.0 Sunny Boy Storage 6.0 aC
connection Rated power (at 230 V, 50 Hz) 3680 W 5000 W1) 6000 W1) 4600 W 6300 W Overload capacity
(at 25°C to max. 60 sec)2) 7500 W 16 A 21.7 A3) AC nominal current output (at 230 V, 50 Hz) 26 A

o SBS3.7-10 (Sunny Boy Storage 3.7) ab Firmware-Version >= 3.00.00.R o SBS5.0-10 (Sunny Boy Storage 5.0) ab Firmware-Version >= 3.00.00.R o SBS6.0-10 (Sunny Boy Storage 6.0) ab Firmware-Version >= 3.00.00.R 1.2 Zielgruppe Dieses Dokument ist für Fachkräfte und Endanwender bestimmt. Die Tätigkeiten, die in diesem

?SMA???????,Sunny Boy Storage????????????????????????????? ????Sunny Home Manager
2.0,??????????????????????,??? ...

SUNNY BOY STORAGE 3.7 / 5.0 / 6.0. Indicaciones sobre este documento. Área de validez. Grupo de destinatarios. Contenido y estructura del documento. Niveles de advertencia. Símbolos del documento. Marcas de texto en el documento. Denominación en el documento. Información adicional. Seguridad.

o SBS5.0-10 (Sunny Boy Storage 5.0) ; partir de la version de micrologiciel >= 3.00.00.R
o SBS6.0-10 (Sunny Boy Storage 6.0) ; partir de la version de micrologiciel >= 3.00.00.R

1.2 Groupe cible Ce document s'adresse au personnel qualifié et aux utilisateurs finaux. Les opérations

identifiées

Datos técnicos Sunny Boy Storage 3.7 Sunny Boy Storage 5.0 Sunny Boy Storage 6.0 Conexión de CA Potencia asignada (a 230 V, 50 Hz) 3680 W 5000 W1) 6000 W1) Capacidad de sobrecarga (a 25 °C hasta máx. 60 s)2) 4600 W 6300 W 7500 W Salida de corriente nominal de CA (a 230 V, 50 Hz) 16 A 21,7 A 26 A

Technische gegevens Sunny Boy Storage 3.7 Sunny Boy Storage 5.0 Sunny Boy Storage 6.0 AC-aansluiting Opgegeven vermogen (bij 230 V, 50 Hz) 3680 W 5000 W1) 6000 W1) Overbelastingcapaciteit (bij 25 °C tot max. 60 s)2) 4600 W 6300 W 7500 W Nominale AC-stroom (bij 230 V, 50 Hz) 16 A 21,7 A 26 A

o SBS6.0-10 (Sunny Boy Storage 6.0) from firmware version >= 3.00.00.R 1.2 Target Group This document is intended for qualified persons and end users. Only qualified persons are allowed to perform the activities marked in this document with a warning symbol and the caption

Dati tecnici Sunny Boy Storage 3.7 Sunny Boy Storage 5.0 Sunny Boy Storage 6.0 Collegamento CA Potenza massima (a 230 V, 50 Hz) 3680 W 5000 W1) 6000 W1) Capacità di sovraccarico (a 25°C fino a max 60 s)2) 4600 W 6300 W 7500 W Corrente nominale CA uscita (a 230 V, 50 Hz) 16 A 21,7 A 26 A

o SBS5.0-10 (Sunny Boy Storage 5.0) a partire dalla versione del firmware >= 4.00.00.R o SBS6.0-10 (Sunny Boy Storage 6.0) a partire dalla versione del firmware >= 4.00.00.R 1.2 Destinatari Il presente documento è destinato a tecnici specializzati e utenti finali. Le operazioni

Caractéristiques techniques Sunny Boy Storage 3.7 Sunny Boy Storage 5.0 Sunny Boy Storage 6.0 Raccordement AC Puissance assignée (pour 230 V, 50 Hz) 3680 W 5000 W1) 6000 W1) Capacité de surcharge (à 25 °C jusqu" à 60 sec. max.)2) 4600 W 6300 W 7500 W Courant de sortie nominal AC (pour 230 V, 50 Hz) 16 A 21,7 A3) 26 A Tension nominale AC / Plage de ...

Technical data (preliminary) Sunny Boy Storage 3.7 Sunny Boy Storage 5.0 Sunny Boy Storage 6.0 AC connection Rated power (at 230 V, 50 Hz) 3680 W 5000 W1) 6000 W1) Overload capacity (at 25°C to max. 60 sec)2) 4600 W 6300 W 7500 W AC nominal current output (at 230 V, 50 Hz) 16 A 21.7 A3) 26 A Nominal AC voltage / AC voltage range 230 V / 172.5 V to 264.5 V

o SBS6.0-10 (Sunny Boy Storage 6.0) from firmware version >= 4.00.00.R 1.2 Target Group This document is intended for qualified persons and end users. Only qualified persons are allowed to perform the activities marked in this document with a warning symbol and the caption

Technische gegevens (onder voorbehoud) Sunny Boy Storage 3.7 Sunny Boy Storage 5.0 Sunny Boy Storage 6.0 AC-aansluiting Opgegeven vermogen (bij 230 V, 50 Hz) 3680 W 5000 W1) 6000 W1) Overbelastingcapaciteit (bij 25°C tot max. 60 s)2) 4600 W 6300 W 7500 W Nominale AC-stroom (bij

230 V, 50 Hz) 16 A 21,7 A3) 26 A Nominale AC-spanning / AC-spanningsbereik ...

Technical data Sunny Boy Storage 3.7 Sunny Boy Storage 5.0 Sunny Boy Storage 6.0 AC connection Rated power (at 230 V, 50 Hz) 3680 W 5000 W1) 6000 W1) Overload capability (at 25°C to max. 60 sec.)2) 4600 W 6300 W 7500 W AC nominal current output (at 230 V, 50 Hz) 16 A 21.7 A3) 26 A Nominal AC voltage / AC voltage range 230 V / 172.5 V to 264.5 V

Web: <https://solar.cgprotection.com>