

Can high-temperature superconductor (HTS) induction heater improve efficiency?

Abstract: The high-temperature superconductor (HTS) dc induction heater shows great potential in the efficiency increase and heating quality improvement, which has been validated by previous prototypes. Now, Shanghai Jiao Tong University has been developing and fabricating an industrial scale 1-MW HTS dc induction heater in China.

What is high-temperature superconducting (HTS)?

High-temperature superconducting (HTS)-based applications have the potential to substantially improve efficiency, performance and/or functionality of all aspects of the power infrastructure, including generation, distribution, grid resilience, consumption and transportation 18.

What is superconducting magnetic energy storage (SMES)?

1. Introduction Superconducting Magnetic Energy Storage (SMES) is a promising high power storage technology, especially in the context of recent advancements in superconductor manufacturing .

What is a superconducting material?

In addition, the superconducting material, which is a complex quaternary oxide, is one of the most chemically advanced materials currently in industrial production. High-performance coated conductors require conductor flexibility, shunting, strengthening and insulating layers and post-engineering.

Are high-temperature superconductors economically viable?

Since the discovery of high-temperature superconductivity 1 at above liquid nitrogen temperature 2 in cuprates, there have been enormous efforts to create practical superconductors that meet industry needs at sufficiently low cost to be economically viable.

What are 2G Superconducting materials?

Second generation (2G) superconducting materials are cuprates of rare earth elements,  $\text{ReBaCuO}$  ( $\text{Re} = \text{Y}, \text{Sm}, \text{Gd}$ ). Compared to 1G HTS, second generation materials can sustain higher critical currents at similar external magnetic fields, thus improving the performance of SMES units.

A superconducting magnetic eddy current heater (SMH) is proposed for the characteristics of wind thermal power generation system, which uses non-resistive, large current-carrying superconducting coils for excitation, ...

This paper thoroughly presents the development of the world's first commercial megawatt HTS DC inducting heater based on 2nd generation HTS tapes, expected to significantly improve the ...

# Superconducting light energy storage heater

light-weighted electrical equipment, high-speed maglev transportation, ultra-strong ... heaters at 65-77 K with liquid nitrogen as coolant and field  $< 1$  T, applications such as motors, generators, ...

Superconducting magnetic energy storage (SMES) plants have previously been proposed in both solenoidal and toroidal geometries. The former is efficient in terms of the quantity of superconductor ...

SAH Solar air heater SE Solar energy SFPC Solar at-plate collector SHM Sensible heat materials SHS Sensible heat storage LHS Latent heat storage PW Paraffin wax HT Heat exchanger SMES ...

The proposed superconducting energy storage needs no current leads, so huge operation loss can be avoided. ... Efficiency analysis of a high-temperature superconducting ...

Web: <https://solar.cgprotection.com>